

Openframe Series

This POS-media display is specifically designed for installation and use at the POS. By the mounting frame allows the monitors installed flush. Such as in

- rack systems
- presentation walls
- showcases
- presentation furniture
- and others



UV-70-SE-OPF



UV-102-SE-OPF

Model:	UV-70-SE-OPF	UV-102-SE-OPF	UV-150-SE-OPF	UV-190-SE-OPF	UV-220-SE-OPF
Panel					
Screensize	7 inch	10 inch	15 inch	19 inch	22 inch
Resolution (Aspect Ratio)	800*480 (16:9)	1024*600 (15:9)	1024*768 (4:3)	1366*768 (16:9)	1920*1080 (16:9)
Brightness (Contrast)	200cd/m ² (500:1)	200cd/m ² (200:1)	400cd/m ² (400:1)	250cd/m ² (1000:1)	250cd/m ² (1000:1)
Viewing Angel (Left/Right/Up/Down)	70°/70°/50°/70°	50°/50°/45°/40°	70°/70°/60°/65°	85°/85°/80°/80°	85°/85°/80°/80°
Functions					
Playback mode	Auto-loop once power on, Repeat one, repeat all				
Motion-Sensor (external)	mute or standby				
Content-Update	Via USB-Drive, or Memory exchange				
Supported formats					
Video	MPEG1(VCD)、MPEG4		MPG、MPG-1、MPG-2、MPG-4, AVI、MP4、RM、RMVB		
Picture	JPEG				
Audio	MP3、WMA	MP3、WMA			
Memory	SD-Card / CF-Card / USB drive				
Speaker	2 x 2 W	2 x 2 W	2 x 2 W	2 x 2 W	2 x 2 W
General Information					
dimensions / weight (WxHxD)	192 x 138 x 25 mm / 718 g	290 x 155 x 32 mm / 1,7 kg	395 x 260 x 35 mm / 3,2 kg	499 x 259 x 33 mm / 3,8 kg	564.6 x 297.2 x 35 mm / 4,8 kg
Vesa					
Power	AC 110-220V DC12V/1A		AC 110-220V DC 12V 4A, 48W		
Accessories	power supply, remote controller, user manual				
Optional accessories					
	Vesa mount adapter				
Other	speaker cable approx 1,5 mtr.				